


Urea Water Transfer Pump for SCR System **TMC/HNP**



This pump is suitable for a use of transfer urea water to use as a reducing agent of a selective catalytic reduction (SCR system) to meet IMO NOx regulation (Tier 3). For main components, stainless steel are used to handle urea water.



Urea Water Transfer Pump for SCR System

TMC/HNP

Outline

NOx regulation: MARPOL Annex VI "International convention for the prevention of pollution from ships". NOx control requirements apply to installed marine diesel engine of over 130 kW output.

Apply Tier 3 Regulation

Tier 3 applies for vessels built after Jan. 2016 operate at ECA (emission control area, North American ECA, within 200 nm., and the United States Caribbean Sea ECA). For vessels built after Jan. 2021, Tier3 applies to North Sea ECA and Baltic ECA.

It is necessary to reduce NOx for 80% compared to tier 1. Thus, in general, after treatment unit on the engine is necessary.

Emission Control Area (ECA)



Baltic Sea and North Sea (SOx only)



North American 200 nm ECA (NOx and SOx)

*SOxECA and NOxECA can be specified separately.

Methods and Technique to Meet NOx Tier 3 Regulation

- SCR: Selective Catalytic Reduction
- EGR: Exhaust Gas Recirculation
- Use of emulsion fuel oil
- Port water injection

Feature of SCR (Selective Catalytic Reduction)

- More than 90% of NOx can be reduced
- Less side effect on engine fuel economy
- Necessary to feed urea water

Process

Supply / spray urea water as a reducing agent for the NOx removal in exhaust gas.

By catalytic action in a reactor, nitrogen oxide is dismantled in harmless nitrogen (N₂) and water (H₂O).

Specification

Centrifugal	TMC-32M
	TMCE-32M (with priming unit)
Screw	HNP-201
	HNP-301
	HNP-401
Material	Pars in contact with fluid is stainless steel
Shaft seal	Mechanical seal, gland packing

	Capacity (m ³ /h)	T. Head (m)	Temperature (°C)
Centrifugal	to 5	40	-10 to 40
Screw	to 5	40	

*If urea water is operate/stored at 40 and above, it may deteriorate drastically.

TAIKO KIKAI INDUSTRIES CO., LTD.

<https://www.taiko-kk.com/en/>

Head Office and Factory 209-1 Shimotabuse, Tabuse-cho, Kumage-gun, Yamaguchi Pref. 742-1598 Japan
TEL: +81-820-52-3113 FAX: +81-820-53-1001
E-mail: business-marine@taiko-kk.com

Tokyo Branch 6th floor, Ichigo Kudan Building, 2-38 Kanda-Jinbo-cho, Chiyoda-ku, Tokyo 101-0051 Japan
TEL: +81-3-3221-8551 FAX: +81-3-3221-8555
E-mail: tokyo-br@taiko-kk.com

Osaka Branch 8th floor, KC Building, 3-4-7 Kawara-machi, Chuo-ku, Osaka 541-0048 Japan
TEL: +81-6-6231-6241 FAX: +81-6-6222-3295
E-mail: osaka-br@taiko-kk.com

Shanghai Resident Office (China)

TAIKO ASIA PACIFIC PTE. LTD. (Singapore) MarFlex BV (the Netherlands)

• The sizes and specifications of the products in this catalog are subject to improvement.

